

Stomacher® 4500 BAM

Product specifications

Model	Stomacher® 4500 BAM
Cat No.	4500/000/EU
Dimensions	480mm wide x 480mm deep x 445mm high (unpacked)
Weight	36kg (unpacked)
Supply Voltage	220-250V
Supply Frequency	50-60Hz
Plug Top Fuse	F5A (UK cord set only)
Mains Inlet Fuses*	T1.0A 250V 5x20mm, breaking capacity: 35A @ 250V
Transformer Fuse*	T250mA 250V 5x20mm, breaking capacity: 35A @ 250V
PCB Fuse*	F2.5A 250V 5x20mm, breaking capacity: 100A @ 250V
Insulation	Class 1 (Earthed)
Installation	Over Voltage Category II
Pollution	Pollution Degree 2
Duty Cycle	Continuous
Rated Load	120W
Disposable Bag Size	380mm x 508mm
Minimum Recommended Capacity	1000ml
Maximum Recommended Capacity	4500ml
Maximum Recommended Sample Temperature	60°C
Recommended Operating Ambient Temperature Range	10-35°C
Recommended Operating Relative Humidity Range	10-89%
Adjustable Timer Settings	0 seconds – 99 minutes, 59 seconds (±5%)
No Load Paddle Speeds (@ nominal 20°C)	125rpm (±5%) LOW 150rpm (±5%) NORM. 175rpm (±5%) HIGH
Paddle Clearance	0-20mm