

Benchmark 

MultiCYCLER™

MULTI-BLOCK THERMAL CYCLERS

- + **Dual or Triple Block Format**
2x48x0.2ml or 3x32x0.2ml options
Each block functions independently
- + **Intuitive Touch Screen Control**
Large 10" adjustable touch screen
Folds away when not in use
- + **Program Wizard**
Fast and easy programming
Advanced programming features
- + **Gradient Capabilities**
Up to 8 temperatures/block



MultiCYCLER™

Multi-Block Thermal Cyclers

Designed for laboratories wanting flexibility in their applications, Benchmark's MultiCycler™ Thermal Cyclers offer multiple, independent cycling blocks in a single unit. Dual or triple block models are available, both offering extremely fast cycling profiles, large touch screen interfaces, self-adjusting heated lids, gradient capabilities, and an easy-to-use program wizard.

All programming features are accessed from the large, 10" full color touch screen. The screen can be angled towards the user when in use and then tucked away to save space. A program wizard guides users through the simple protocol set up process. Advanced programming features include gradient, adjustable ramp rates, and time increments and decrements. For multi-user labs, password protection prevents interference of an existing run. A USB provides for unlimited program storage and easy transfer of protocols between MultiCycler machines.

The auto-adjusting heated lid prevents condensation and evaporation of samples. Lid temperature can be programmed, and when the block temperature is below 35°C, the lid automatically shuts off. Peltier units allow for exceptionally fast heating and cooling of the blocks. Temperature change is precisely and accurately controlled within tight tolerances by a proprietary algorithm that simulates sample temperature, resulting in fast runs and reproducible results.

The wells are arranged in a 4x8 and 6x8 format, allowing for the use of PCR strip tubes in both models. Each block is independently controlled.



Adjustable Screen



Quick and Easy Programming



Independent Blocks

Technical Data:

Capacity:

MultiCycler 332: 3x32 well blocks
 MultiCycler 248: 2x48 well blocks
 All accept 0.2mL PCR tubes and strips, flat or dome caps

Heating and Cooling:

Peltier elements

Display:

10" full color touch screen with adjustable angle

Comm Ports:

USB 2.0 and LAN

Block Temp Range:

4°C - 99.9°C

Max. Heating Rate:

7.5°C/sec

Max. Cooling Rate:

6°C/sec

Temp. Uniformity:

±0.2°C (at 90°C)

Temp. Accuracy:

±0.2°C (at 90°C)

Ramp Rate Adjustment:

0.1 - 5.0°C

Gradient Functionality:

Yes, 8 different temps/block

Gradient Accuracy:

±0.1°C

Gradient Range:

30 - 99.9°C

Heated Lid:

Yes

Lid Temp. Range:

30-112°C

Power:

100-240V, 50-60Hz

Dimensions (L x W x H):

37.5 x 27 x 27.7cm
 14.75 x 10.5 x 10.9in

Weight:

28.7lbs, 13kg

Warranty:

2 years

Ordering Information:

T3-0248G* MultiCycler 248, Dual block gradient thermal cyler, 2x48 well blocks

T3-0332G* MultiCycler 332, Triple block gradient thermal cyler, 3x32 well blocks

*Supplied with US plug. For EU plug, please add (-E) to item number.

Also available:

Benchmark offers both full size and mini thermal cyclers as well as a full complement of PCR and qPCR reagents



Benchmark Scientific

PO Box 709, Edison NJ 08818

TEL: 908 769-5555 Fax 732 313-7007

Web: www.BenchmarkScientific.com

Email: info@BenchmarkScientific.com

Effective December 2022. Subject to change without notice. slj1222