PORTWEST

PRODUCT SPECIFICATION & TECHNICAL DATA

P251 - FFP2 Valved Fold Flat Respirator

Collection: Disposable Mask FFP2

Range: Disposable Masks

Inner Pack: 20 Outer Carton: 30

Product information

Comfort: Vertical Flat Folded, each mask is packed inside an individual polybag for easier storage. Exhalation valve for lighter breathing resistance. Adjustable nose clip for optimised fit. Ultrasound welded elastic bands.

Disposable Mask FFP2

Disposable mask FFP2 level, protects against solid and liquid particles of average toxicity. Minimal % of filtration 94%. Protects up to 10 times the TLV (Assigned Protection Factor for FFP2 masks). Examples of applications: Sanding of soft wood, composite materials, rust, putty, plaster, plastics /cutting, deburring, grinding, drilling of metal. Our Biztex brand ensures exceptional quality and performance across our full range of disposable masks.

Disposable Masks

Our Biztex™ brand ensures exceptional quality and performance across our full range of disposable masks. The extensive Biztex range offers a high level of protection and quality safeguarding the wearer against many workplace risks including liquid chemicals, static electricity, dry particles and radioactive contamination. The complete Biztex range includes disposable masks and limited-life garments.

Standards

EN 149 FFP2 (NR)



Features

- CE-CAT III
- Flexible shape which allows the mask to be folded flat
- · Ultrasound welded elastic strap
- · Ideal for all day use
- Individually packed for vending machines
- Individually wrapped inside hygienic polybag
- Retail box which aids presentation for retail sales

	Range						
White	-						

PORTWEST_®

PRODUCT SPECIFICATION & TECHNICAL DATA

P251 - FFP2 Valved Fold Flat Respirator Commodity Code: 6307909311

Test House

BSI Group The Netherlands B.V. (Notified Body No.: 2797) Say Building, John M. Keynesplein 9, 1066 EP , Netherlands Cert No: 714896

CARTON DIMENSIONS/WEIGHT

Item	Colour	Len	Wid	Hgt	Weight (Kg)	Cubic (m³)	EAN13	DUN14
P251WHR	White	66.0	43.0	43.0	0.3400	0.1220	5036108160037	15036108635853