

Specifications	Model Number
	TSG700RESBW
Application, Rating and Electrical Data	
Application	Storage of General (non-flammable) Laboratory Materials
Storage Volume	620Liters / 21.9 Cubic Feet
Factory Set Point	+5 °C
Set Point / Increment	+5 °C / 0.1 °C
Electrical Power / Rated Current	230V 50 Hz 1 Phase / 1.6A
Building Supply Rating	13A 250V
Power Plug/Power Cord Length	13 Amp 250V / 4 Meters (13 feet)
Agency Listings	CE
Standards and directives	2006/42/EC, 2014/30/EU, 2014/35/EU, 2011/65/UE, 2015/863/EU & 2012/19/EU
Electromagnetic Compatibility	Emissions (Class A), Immunity (Industrial Environment)
Indoor/Outdoor Usage	Indoor Use Only
Application Environment	Non-Corrosive, Non-Flammable, Non-Explosive, Good Air Ventilation
Ambient Operating Temperature	15° C to 32° C (59° F to 90° F)
Refrigeration Configuration	
Refrigeration System	Vapor compression system
Compressor / Number / Capacity	Single speed / 1 / 236W
Condenser Type/Number	Forced-Air Cooled Finned-Tube Coil Heat Exchanger / 1
Expansion Device	Capillary Tube
Evaporator Type / Defrost Method	Forced Air Finned-Tube Coil Heat Exchanger / Automatic Defrost
Refrigerant Charge / Flammability	R290,90gms,GWP:3 ODP:0 / Flammable
Controller/Electrical System Configuration and Features	
Controller Level	Eye Level
Power Switch	On the Controller Main Screen
Controller Type	Electronic Controller with LCD display
Setpoint Security / Programmable	Yes / Yes
Compressor Safe Guard	Overload Protection (OLP)
Control Sensor	NTC Probe
Connectivity / Remote Outputs Terminals	Dry Contact (NO and NC)
Adjustable Warm / Cold Alarms	Fully Adjustable
Power Failure Alarm	Acoustic and Visual
Electronic Chart Recorder	Not Provided
Dimensions and Construction	
Interior Dimensions (H x D x W)	1505 mm x 686 mm x 600 mm (59.2" x 27" x 23.6")
Exterior Dimensions (H x D x W)	2085 mm x 826 mm x 750 mm (82.1" x 32.5" x 29.5")
Insulation	7.5 cm (2.95") Polyurethane Foam
Door Perimeter heater	No
Shelves / Load Limit	4 Shelves / 30kg (66 lbs) per Shelf
Casters	2 Lockable Castors at the front & 2 Fixed Castors at the rear
Non-Crated Shipping Weight	152kgs / 335.1 lbs

Typical Performance Characteristics																												
<p>Set Point 5°C @ 20°C Ambient</p> <p>Pull Down and Warm Up</p>	<p>Set Point 5°C @ 20°C Ambient</p> <p>At 5C Cycle</p>	<p>Test Unit Series Number or MSO Number: 20297-A-9-5</p> <table border="0"> <tr> <td>Cabinet Load:</td> <td>Unloaded</td> </tr> <tr> <td>Average Cabinet Temp at 5C Cycle (C):</td> <td>4.99</td> </tr> <tr> <td>Peak Variation from Setpoint (C):</td> <td>-4.3 / 1.8</td> </tr> <tr> <td>Uniformity (C):</td> <td>1.11</td> </tr> <tr> <td>Stability (C):</td> <td>4.27</td> </tr> <tr> <td>1-min Door Opening Recovery (min):</td> <td>7.9</td> </tr> <tr> <td>Cycle on Time(%):</td> <td>14.9</td> </tr> <tr> <td>Cycle (on/off) Time (min):</td> <td>4.9/28</td> </tr> <tr> <td>Energy Consumption (kw-hr/day):</td> <td>1.17</td> </tr> <tr> <td>Heat Rejection Rate (btu/hr):</td> <td>165.88</td> </tr> <tr> <td>Pull Down Time to setpoint:(Min)</td> <td>25.9</td> </tr> <tr> <td>Warm Up Time to 15C (min):</td> <td>239</td> </tr> <tr> <td>Sound (dBA):</td> <td>47.8</td> </tr> </table>	Cabinet Load:	Unloaded	Average Cabinet Temp at 5C Cycle (C):	4.99	Peak Variation from Setpoint (C):	-4.3 / 1.8	Uniformity (C):	1.11	Stability (C):	4.27	1-min Door Opening Recovery (min):	7.9	Cycle on Time(%):	14.9	Cycle (on/off) Time (min):	4.9/28	Energy Consumption (kw-hr/day):	1.17	Heat Rejection Rate (btu/hr):	165.88	Pull Down Time to setpoint:(Min)	25.9	Warm Up Time to 15C (min):	239	Sound (dBA):	47.8
Cabinet Load:	Unloaded																											
Average Cabinet Temp at 5C Cycle (C):	4.99																											
Peak Variation from Setpoint (C):	-4.3 / 1.8																											
Uniformity (C):	1.11																											
Stability (C):	4.27																											
1-min Door Opening Recovery (min):	7.9																											
Cycle on Time(%):	14.9																											
Cycle (on/off) Time (min):	4.9/28																											
Energy Consumption (kw-hr/day):	1.17																											
Heat Rejection Rate (btu/hr):	165.88																											
Pull Down Time to setpoint:(Min)	25.9																											
Warm Up Time to 15C (min):	239																											
Sound (dBA):	47.8																											


1) Performance is nominal and individual units may vary.  
 2) Product performance will differ due to product amount, product size and operating conditions.  
 3) Continuous product enhancements may, without notice, result in amendments or omissions to this specification. Thermo Scientific cannot accept responsibility for damage, injury, loss or expenses resulting from misapplication of the information herein.



**Typical Cabinet Temperature Map**  
 Refrigerator 22cuft , 3 Inner-Shelves + Base, Single Outer Door


Temperatures are averages during > 20 cycles after reaching a setpoint of 5C

**Top View of Shelves**



**Cabinet Average:** 5.1 C  
**Probe Average:** 6.2 C  
**Peak Variation:** +1.8 C / -3.9 C

**Front View**



20297-A-9-5

	M1	M2	M3	M4	M5	M10	M11	M12
Avg	5.7	5.7	5.5	5.2	5.6	5.1	5.1	9.3
Max	6.7	6.8	6.8	6.6	6.7	6.3	6.2	20.2
Min	3.9	3.6	2.1	1.1	3.1	3	3.2	1.1

	M13	M14	M15	M16	M17	M18	M19	M20
Avg	9.2	4.8	5	5.2	5	4.8	4.8	4.8
Max	20.2	6.2	6.1	6.2	6.2	6	6	6
Min	0.4	1.8	2.9	3.3	2.3	2.1	2.5	2.8

ONLY CABINET SHOWN FOR CLARITY IN TOP VIEW,  
TO ILLUSTRATE INTERIOR DIMENSIONS

thermo scientific

